



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperatuer Range: -25°C ~ +85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A2026-02Y	2.00	6.00
A2026-03Y	4.00	8.00
A2026-04Y	6.00	10.00
A2026-05Y	8.00	12.00
A2026-06Y	10.00	14.00
A2026-07Y	12.00	16.00
A2026-08Y	14.00	18.00
A2026-09Y	16.00	20.00
A2026-10Y	18.00	22.00
A2026-11Y	20.00	24.00
A2026-12Y	22.00	26.00
A2026-16Y	30.00	34.00

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENEAL TOLERANCE		制图 DRAWING	钱岳生 2014、10、20		料号 PART NO.	A2026-nY		版本 REV.	A
			X.±0.25	X.*±2'	审核 CHECK	张名 2014、10、21		品名 TITLE	PA孔座		页次 SHEET	1/1
			.XX±0.20	.X'±1'	核准 APPROVAL	张名 2014、10、23		客户料号 CUTM. NO.	深圳市金航标电子有限公司		www.kinghelm.com.cn	
			.XX±0.15	.XX'±0.5'	单位 UNITS	MM	比例 SCALE	1:1	KH-A2026-03Y		0755-28190160	
			.XXX±0.10	.XXX'±0.5'								