


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Connector Type = Universal Ejection
- ? Pin Headers
- ? Standard Profile
- ? Number of Positions = 14
- ? 2.54 x 2.54 mm Centerline, Matrix
- ? PCB Mount Angle = Vertical

[Check Pricing & Availability](#)
[Search for Tooling](#)
[View Mating Products \(12\)](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

[HEADER ASSY, UNIVERSAL, AMP -LATCH](#) (PDF, English)

? None Available

[AMP-LATCH* and IDC Header Connectors, .100 x .100 In...
\(PDF, English\)](#)

? None Available

? None Available

- ? 2D Drawing (DXF, Version C)
- ? 3D Model (IGES, Version C)
- ? 3D Model (STEP, Version C)

? Product Line Information

- ? Tooling
- ? Mating Products (12)

List all Documents

- ? Connector Type = Universal Ejection Pin Headers
- ? Profile = Standard
- ? Number of Positions = 14
- ? PCB Mount Angle = Vertical
- ? PCB Retention Feature = No
- ? Mating Polarization Method = Center, Dual Polarizing Bar, Military
- ? Mating Connector Lock = With
- ? Housing Style = 4 - Sided
- ? Ejection Latches = With
- ? Post Size (mm [in]) = 0.64 [.025]
- ? Shrouded = Yes
- ? PCB Thickness (mm [in]) = 3.18 [0.125]
- ? Mating Polarization = With
- ? Latch Type = Long
- ? Mating Connector Lock Type = Latch

? Termination (Solder) Post Length (mm [in]) = 3.94 [0.155]

? Solder Tail Contact Plating = Tin over Nickel

? Centerline, Matrix (mm [in]) = 2.54 x 2.54
[.100 x .100]

? Contact Mating Area Plating = Gold (30) over Nickel, Gold Flash over Palladium Nickel

? Contact Shape = Square

? Housing Material = Thermoplastic
 ? Housing Flammability Rating = UL 94V -0
 ? Housing Color = Blue

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Temperature Rating = Standard

? Brand = AMP