


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Socket
? Terminal Style = Printed Circuit
? Terminal Type = Contact
? Lead Size Accepted = .41 mm
? Lead Length Accepted = 3.96 - 5.54
mm

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

[SOCKET, 8 PIN PRINTED CIRCUIT](#) (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

List all Documents

Additional Information:

? Product Line Information

Related Products:

? Tooling

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Socket
- ? Terminal Type = Contact
- ? Product Series = 8058 Series
- ? Sleeve Material = Brass
- ? Profile = Low

Electrical Characteristics:

- ? Pin Circle Diameter (mm [in]) = 5.84 [0.230]

Termination Related Features:

- ? Terminal Plating = Gold

Body Related Features:

- ? Terminal Style = Printed Circuit
 ? Number of Terminals = 8
 ? Post Diameter (mm [in]) = 0.51 [0.020]
 ? Socket Type = TO -5
 ? Terminal Material = Beryllium Copper
 ? Insulator Material = Teflon

Contact Related Features:

- ? Sleeve Plating = Gold

Configuration Related Features:

- Lead Size Accepted (mm [in]) = 0.41 [0.016]

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Operating Temperature (°C) = -55 – +125

Other:

- ? Brand = AMP