

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Contact
? Contact Type = Micro - Timer II
? Receptacle
? Wire Range = 0.50 -1.00 ² [20-17] mm
[AWG]
? Insulation Diameter = 1.40 - 2.10 mm

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

[PRODUCT GROUP DRAWING FOR MICRO TIMER 2 CONTACT TYPE](#)
[A](#) (PDF, German)

? None Available

? None Available

? None Available

? None Available

? None Available

? Product Line Information

? Line Drawing

? Tooling

List all Documents

? Product Type = Contact

? Gender = Receptacle

? Insulation Diameter (mm [in]) = 1.40 – 2.10
[0.055 – 0.083]

? Tab Fit (mm [in]) = 1.60 x 0.61 [.063 x .024]

? Comment = Modified Cantilever Springs

? Wire Range (mm [AWG]) = 0.50 -1.00 ² [20-17]
 ? Single Wire Sealing System = Yes
 ? Insulation Type = FLK, FLR
 ? Cantilever Spring Material = Stainless Steel

? Contact Type = Micro -Timer II

? Contact Material = CuFe2

? Contact Mating Area Plating Material = Pre -Tin

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Wire

? Packaging Method = Loose Piece

? Packaging Quantity = 500

? GET 0.64 Connector System = No

? Brand = AMP