






Straight Blade Devices

15 and 20 Ampere, 125, 250 Volts and 277 Volts AC

2 Pole, 2 Wire Non-Grounding and 2 Pole, 3 Wire Grounding

Plugs, Connector Bodies and Receptacles**HBL5865VY****HBL5869VY****HBL5302****HBL5929****HBL9758VY****HBL5552B****15A, 125V
2 Pole, 2 Wire
Valise® Plugs****IP20**
SUITABILITY**15A 125V
NEMA 1-15R
UL CSA
0.5 HP****15A 125V
NEMA 1-15P
UL CSA
0.5 HP**

Description	Cord Diameter	Catalog Numbers	
Yellow nylon, non-polarized.	.218"-.385" (5.5-9.8)	-	HBL5865VY
Yellow nylon, polarized.	.218"-.385" (5.5-9.8)	-	HBL5866VY

Valise® Connector Bodies

Description	Cord Diameter	Catalog Numbers	
Yellow nylon.	.218"-.385" (5.5-9.8)	HBL5869VY	-

**15A, 277V
2 Pole, 3 Wire
Plug****15A 277V AC
NEMA 7-15R
UL CSA
2 HP****15A 277V AC
NEMA 7-15P
2 HP**

Description	Cord Diameter	Catalog Numbers	
Finger grip, black elastomer.	.312"-.468" (7.9-11.9)	-	HBL5929*

Receptacle, Duplex

Description	Catalog Numbers
Flush, brown, back & side wired.	HBL5302 -

Notes: Horsepower ratings are AC only.

*Not UL listed.

See page A-44 for accessories.

**20A, 250V
2 Pole, 2 Wire
Valise® Plugs****IP20**
SUITABILITY**20A 250V
NEMA 2-20R
UL Listed
2 HP****20A 250V
NEMA 2-20P
UL Listed
2 HP**

Description	Cord Diameter	Catalog Numbers	
Yellow nylon.	.220"-.660" (5.6-16.8)	-	HBL9758VY

Receptacle, Single

Description	Catalog Numbers
Black phenolic.	HBL5552B -

Notes: Horsepower ratings are AC only and apply to plugs and receptacles only.

See page A-44 for accessories.