

Products



What can we help you find?

Support Center

■ Share



Email

Home > Products > Two-Piece, High-Speed Connectors > Product Feature Selector > Product Details

## 2007811-3 Product Details

Industries

Impact High Density Backplane Connectors Always EU RoHS/ELV Compliant (Statement of Compliance) Product Highlights:

Resources

- Impedance = 100 Ω
- Board-to-Board Configuration = Right Angle
- Connector Style = Header
- Header Type = Fully Shrouded
- PCB Mounting Orientation = Vertical

About TE

View all Features







Innovation



# Quick Links-

- Pricing & Availability
- Search for Tooling
- Product Feature Selector

Print

Contact Us About This Product

TE Internal Number: 2007811-3



2007811-3









My Account





#### Documentation & Additional Information

#### Product Drawings:

IMPACT, 4 PAIR, 10 COLUMN, HEADER LEFT GUIDED, RIGHT... (PDF, English)

#### Catalog Pages/Data Sheets:

None Available

#### Product Specifications:

None Available

#### Application Specifications:

None Available

#### Instruction Sheets:

None Available

#### CAD Files:

None Available

# Related Products:

Tooling

#### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- PCB Mounting Orientation = Vertical
- PCB Mount Retention Type = Action/Compliant Tail and Screw(s)
- PCB Mount Alignment Type = Locating Post(s)
- Shrouded = Yes
- UL File Number = E28476

### Electrical Characteristics:

- Impedance (Ω) = 100
- Operating Voltage Reference = AC/DC
- Operating Voltage (VAC) = 120
- Operating Voltage (VDC) = 120

### Termination Features:

Tail Length (mm [in]) = 1.2 [0.047]

## Dimensions:

- PCB Hole Diameter (mm [in]) = 0.39 [0.015]
- Length (X-Axis) (mm [in]) = 26.90 [1.0591]
- Width (Z-Axis) (mm [in]) = 20.80 [0.819]
- Profile Height (Y-Axis) (mm [in]) = 11.95 [0.470]

### Body Features:

Header Type = Fully Shrouded

### Contact Features:

- Contact Length (mm [in]) = 5.50 [0.217]
- Contact Plating, Termination Area, Material = Matte Tin
- Contact Plating, Termination Area, Thickness (μm [μin]) = 1.27 [50]
- Contact Type = Pin

### **Housing Features:**

- Connector Style = Header
- End Wall Location = Right
- Housing Color = Black
- UL Flammability Rating = UL 94V-0

# Configuration Features:

List all Documents

- Number of Differential Pairs Per Column = 4
- Number of Columns = 10
- Guide Location = Left
- Number of Rows = 12
- Number of Positions = 120
- Connector Contact Configuration (No. of Pos./Type) = 80/Signal,

### Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- UL Rating = Recognized
- CSA Certified = Yes

### Environmental:

Operating Temperature (°C [°F]) = -55 - +85 [-67 - +185]

## Conditions for Usage:

Board-to-Board Configuration = Right Angle

### Operation/Application:

Industry Application = Networking (Communications)

### Packaging Features:

Packaging Method = Tube

### Other:

Brand = TE Connectivity

Corporate Information

About TE Investors News Room Supplier Portal Careers

Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center

Customer Support Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed



Terms & Conditions Privacy Policy

© 2013 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved

Site Map

