



Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFMilitary Gra ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'H200X034H3T'

Your search criteria matched only one product, shown below

H200X034H3T



- Labels offer crisp, clear legends with superior legibility
- Meets UL Standard 224 for flammability and AMS -DTL-23053/5C (Class 1 and Class 3)
- Will meet MIL-M-81531, MIL-STD202F, and MIL-STD-883E when printed with RMH4BL or RHH4BL-S ribbons
- Shrink ratio 3:1
- Pre-cut flattened polyolefin is both thermal transfer and dot matrix printable and supplied roll mounted on plastic carrier
- *PANDUIT* labeling software packages include all label formats for quick and easy label production

Part Number	H200X034H3T
RoHS Compliancy Status	Compliant
Part Description	Black, 3/16" diameter polyolefin, 500/roll.
Material	3:1 Flattened Polyolefin
Color	Black
Length (In.)	.34
Length (mm)	8.64
Width (In.)	2.00
Width (mm)	50.80
Max. Wire O.D. (In.)	.19
Max. Wire O.D. (mm)	4.83
Min. Cable O.D. (In.)	.06
Min. Cable O.D. (mm)	1.52
Nominal Cable O.D. (In.)	.06 - .18
Nominal Cable O.D. (mm)	1.52 - 4.83
Pricing Description	Heat Shrink Label, 0.19" (4.83mm) Dia., Black
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.