

## PCB terminal block - MPT 0,5/ 8-2,54 - 1725711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The figure shows a 10-position version of the product

PCB terminal block, Nominal current: 6 A, Nom. voltage: 160 V, Pitch: 2.54 mm, Number of positions: 8, Connection method: Screw connection with tension sleeve, Mounting: Wave soldering, Conductor/PCB connection direction: 0 °, Color: green

### Product Features

- Single-row type with horizontal connection direction
- Use in miniature modules with high contact density
- MICRO PCB terminal block with 2.54 mm IC pitch



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 017918 116316 |
| Weight per Piece (excluding packing) | 2.4 g   |
| Custom tariff number                 | 85369010  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                          |              |
|--------------------------|--------------|
| Length                   | 6.2 mm       |
| Pitch                    | 2.54 mm      |
| Dimension a              | 17.78 mm     |
| Constructional height    | 9 mm         |
| Length of the solder pin | 3.5 mm       |
| Pin dimensions           | 0,5 x 0,9 mm |

# PCB terminal block - MPT 0,5/ 8-2,54 - 1725711

## Technical data

### Dimensions

|               |        |
|---------------|--------|
| Hole diameter | 1.1 mm |
|---------------|--------|

### General

|  |                     |
|--|---------------------|
| Range of articles                      | MPT 0,5             |
| Insulating material group              | I                   |
| Rated surge voltage (III/3)            | 1.5 kV              |
| Rated surge voltage (III/2)            | 1.5 kV              |
| Rated surge voltage (II/2)             | 2.5 kV              |
| Rated voltage (III/3)                  | 63 V                |
| Rated voltage (III/2)                  | 160 V               |
| Rated voltage (II/2)                   | 320 V               |
| Connection in acc. with standard       | EN-VDE              |
| Nominal current $I_N$                  | 6 A                 |
| Nominal cross section                  | 0.5 mm <sup>2</sup> |
| Maximum load current                   | 6 A                 |
| Insulating material                    | PA                  |
| Solder pin surface                     | Sn                  |
| Flammability rating according to UL 94 | V0                  |
| Stripping length                       | 4.5 mm              |
| Number of positions                    | 8                   |
| Screw thread                           | M1,6                |
| Tightening torque, min                 | 0.12 Nm             |
| Tightening torque max                  | 0.15 Nm             |

### Connection data

|  |                      |
|--|----------------------|
| Conductor cross section solid min.   | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.   | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                      | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 0.34 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.34 mm <sup>2</sup> |
| Conductor cross section AWG min.   | 26                   |
| Conductor cross section AWG max.   | 20                   |
| 2 conductors with same cross section, solid min.                           | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                           | 0.34 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded min.                        | 0.14 mm <sup>2</sup> |

# PCB terminal block - MPT 0,5/ 8-2,54 - 1725711

## Technical data

### Connection data

|   |                      |
|---|----------------------|
| 2 conductors with same cross section, stranded max. | 0.34 mm <sup>2</sup> |
|---|----------------------|

### Standards and Regulations

|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CSA    |
| Flammability rating according to UL 94 | V0     |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141109 |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |
| eCl@ss 9.0 | 27440401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121432 |
| UNSPSC 13.2   | 39121432 |

## Approvals

### Approvals

---

Approvals

CSA / EAC / EAC / cULus Recognized / cULus Recognized

---

# PCB terminal block - MPT 0,5/ 8-2,54 - 1725711

## Approvals


Ex Approvals

---

Approvals submitted

---


## Approval details

|   |       |
|---|-------|
| CSA  |       |
|   | B     |
| mm <sup>2</sup> /AWG/kcmil  | 28-20 |
| Nominal current I <sub>N</sub>  | 6 A   |
| Nominal voltage U <sub>N</sub>  | 125 V |

EAC

EAC


|                                |       |
|--------------------------------|-------|
| cULus Recognized               |       |
|                                | B     |
| mm <sup>2</sup> /AWG/kcmil     | 30-20 |
| Nominal current I <sub>N</sub> | 6 A   |
| Nominal voltage U <sub>N</sub> | 125 V |

cULus Recognized 

## Drawings

# PCB terminal block - MPT 0,5/ 8-2,54 - 1725711

Drilling diagram



Dimensional drawing

