



RELAYS, CONTACTORS & SWITCHES

DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE)

ADP08STR04=PIANO DIP SWITCH

Alcoswitch | Alcoswitch DIP , Alcoswitch DIP ADP & ADPA

2-1571999-9

TE Internal Number: 2-1571999-9

Alias ID: ADP08STR04

EU RoHS Compliant

EU ELV Compliant

Product Type Switch

Contact Mating Area Plating Material Gold

Housing Color Black

Housing Material Polyphenylene Sulfide (PPS)

Auto-Insertable Yes

PRODUCT DRAWING

English

3D PDF

DOCUMENTATION

Product Drawings

DIP SWITCH ASSEMBLY ADP/PA SERIES

PDF

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF

English

Product Environmental Compliance

TE Material Declaration

MD_2-1571999-9_04092014725_dmtec

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type Switch

Sealed No

Switch Type DIP

Actuator Style Piano (Side Actuated)

Configuration Features

Number of Switches 8

Configuration (Pole-Throw) Single Pole - Single Throw

Number of Positions 8

Electrical Characteristics

Voltage Rating (VDC) 5

Body Features

Actuator Color White

Contact Features

Contact Mating Area Plating Material Gold

Auto-Insertable Yes

Contact Current Rating (A) 1

Contact Base Material Copper Alloy

Contact Mating Area Plating Thickness (µin) 1.2

Solder Tail Contact Plating Gold over Nickel

Termination Features

Termination Post Length 4 mm [.157 in]

Termination Style Outside L

Mechanical Attachment

Mounting Type Surface Mount

Mounting Angle Vertical

Housing Features

Housing Color Black

Housing Material Polyphenylene Sulfide (PPS)

Centerline 2.54 mm [.1 in]

On Position Lever Down

Dimensions

Length 22.3 mm [.878 in]

Height 6 mm [.236 in]

Usage Conditions

Operating Temperature Range (°C) -30 – 85

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity 500

Packaging Method Tape & Reel

PRODUCT COMPLIANCE



Statement of Compliance

[Statement of Compliance](#)

PDF