



PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke

Product Search

Submit

▶ HPPC06030

Home > Products > Power Inductor > HPPC06030



Part Number : HPPC06030-1R0M-Q8

Structure	Closed Magnetic Circuit Type- Molding Processing & for Ultra High Current
Inductance(?H)	1
Tolerance(±%)	20
Test Frequency	1MHz,0.5V
RDC(?)Max	0.0053
Isat(A)Typ	19
Isat(A)Max	17
Irms(A)Typ	15
Irms(A)Max	14
Operating Temperature	－ 5 5℃～ 1 2 5℃(Including self - temperature rise)
L(mm)	6.8±0.2
W(mm)	7.3±0.2
T(mm)	2.8±0.2

- 1.Irms DC current (A) that will cause an approximate ?T of 40°C.
- 2.Isat DC current (A) that will cause Lo to drop approximately 30%

P/N	HPPC06030-1R0M-Q8
Part Numbering	
Dimensions	
Reflow Profile	
Packing	  
Recommended Pattern	
Electrical Characteristics Curve	

Back

