



SIMATIC IOT2050; 2x Gbit Ethernet RJ45; Display port; 2x USB2.0; 16 GB eMMC; SD card slot; 24 V DC industrial power supply

General information	
Product type designation	IOT2050
Installation type/mounting	
Design	IoT Gateway, built-in unit
Supply voltage	
Type of supply voltage	12/24 V DC
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms
Processor	
Processor type	ARM TI AM6548 HS
Graphic	
Graphics controller	Integrated
Drives	
Slot for drives	1x microSD card slot
Memory	
Type of memory	DDR4
Main memory	2 GB RAM
Capacity of main memory, max.	2 Gbyte
Hardware configuration	
Slots	
<ul style="list-style-type: none"> free slots 	1x Arduino, 1x mPCIe
Digital inputs	
Number of digital inputs	20
Input voltage	
<ul style="list-style-type: none"> Type of input voltage 	DC
Digital outputs	
Number of digital outputs	20
Output voltage	
<ul style="list-style-type: none"> Type of output voltage permissible voltage at output, min. permissible voltage at output, max. 	DC 3.3 V 5 V
Analog inputs	
Number of analog inputs	6
Input ranges	
<ul style="list-style-type: none"> Voltage 	Yes; 0 ... 5 V
Interfaces	
PROFIBUS/MPI	can be implemented with plug-in card
Number of industrial Ethernet interfaces	2
Number of PROFINET interfaces	2
USB port	2x USB 2.0

Connection for keyboard/mouse	USB
serial interface	1x COM (1x RS 232 / 422 / 485)
Video interfaces	
• Graphics interface	1x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	2x Ethernet (RJ45)
— 100 Mbps	Yes
— 1000 Mbps	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Watchdog	Yes
• Status LEDs	Yes
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±4 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m for 80 ... 1 000 MHz, 80 % AM according to IEC 61000-4-3; 3 V/m for 1.4 ... 6 GHz, 80 % AM according to IEC 61000-4-3
Interference immunity to cable-borne interference	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables >30m	±2 kV acc. to IEC 61000-4-5, surge, length > 30 m
• Interference immunity on signal cables < 30m	±1 kV acc. to IEC 61000-4-4, Burst
Interference immunity against voltage surge	
• asymmetric interference	±2 kV acc. to IEC 61000-4-5, surge asymmetric
• symmetric interference	±1 kV acc. to IEC 61000-4-5, surge symmetric
Degree and class of protection	
IP degree of protection	IP20
IP (all-round)	IP20
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
EMC	CE, EN 61000-6-4:2007 +A1:2011, EN 61000-6-2:2005, CE, EN IEC 61000-6-4:2019, EN IEC 61000-6-2:2019
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• Relative humidity	5 ... 85 % at 30 °C, no condensation
• Operation, max.	85 %
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	tested according to IEC 60068-2-6: 10 cycles; 5 to 8.4 Hz: deflection 3.5 mm; 8.4 to 200 Hz: acceleration 9.8 m/s ²
Shock testing	
• Shock load during operation	Tested according to IEC 60068-2-27: 150 m/s ² , 11 ms
Operating systems	
pre-installed operating system	SIMATIC Industrial OS
without operating system	No

Mechanics/material

Enclosure material (front)	plastic
• Plastic	Yes
• Aluminum	Yes
• Stainless steel	Yes
• Glass	No

Dimensions

Width	37 mm
Height	142 mm
Depth	100 mm

last modified:3/12/2024 