

Cable feed-through plates - MC-3/7-MULTI-67-PV-LG - 1415234

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable feed-through plates, no. of conductors: 7, length: 222 mm, width: 92 mm, height: 43 mm, external cable diameter: 1x 30 mm ... 60 mm, color: gray



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 039404
GTIN	4055626039404
Weight per Piece (excluding packing)	280.000 g
Custom tariff number	39269097
Country of origin	Finland

Technical data

Dimensions

Length	222 mm
Width	92 mm
Height	43 mm
Drill hole distance, horizontal	62 mm
Drill hole distance, vertical	194 mm
External cable diameter	1x 30 mm 60 mm
	4x 8 mm 16 mm
	2x 24 mm 54 mm

Ambient conditions

Degree of protection	IP66 (Minimum sheet thickness >= 2.5 mm)
	IP67 (Minimum sheet thickness >= 2.5 mm)



Cable feed-through plates - MC-3/7-MULTI-67-PV-LG - 1415234

Technical data

Ambient conditions

°C
neet steel ()
Nm (Mounting screws)
g screws
screw, torque: 1.5 - 2.0 Nm, SW5 Allen key
g screws included should be used for assembly. pps: tes with the mounting screws provided (observe torque) le in the membrane (with a screwdriver) or cut off the tip of cable through the opening (from the outside). Withdraw the imately 20 mm (to improve strain relief).

Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values


Drawings

China RoHS




Cable feed-through plates - MC-3/7-MULTI-67-PV-LG - 1415234

Dimensional drawing



Wall cutout drawing

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 5.1	23110102
eCl@ss 6.0	23110102
eCl@ss 8.0	27409208
eCl@ss 9.0	27400569

ETIM

ETIM 5.0	EC001004

Phoenix Contact 2018 @ - all rights reserved http://www.phoenixcontact.com