



Home > Products > Discrete Thermistors > 194 > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 194-222LET-D02



Actual product appearance may vary.

**Uni-Curve with insulated leads and epoxy**

### Features

Accuracy  
High stability  
Long life  
Cost effective  
Small size  
Epoxy coated

### Potential Applications

Temperature measurement, indication and control  
Compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices  
Medical

### Description

194 Series Thermistors are high quality, low-cost resistance, temperature matched interchangeable units. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems. These product are the same as the 192 Series, except the leads are Teflon-coated.

### Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 °F]	2,252 Ohm
Tolerance	± 0,2 °C [0.36 °F]
Accuracy	0 °C to 70 °C [32 °F to 158 °F]
R- T Curve	16
Operating Temperature Range	-60 °C to 150 °C [ -76 °F to 302 °F]
Maximum Diameter	2,413 mm [0.095 in]
Termination Material	30 Gauge solid nickel, Teflon insulated
Lead length	38,1 mm [1.50 in]
Time Constant in Air	15.0 s
Dissipation Constant	0,75 m/W°C
Series Name	194

### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)