



<div> <div>Circuit Board Indicators</div> <div>Panel Mount Indicators</div> <div>Solid State Lighting</div> <div>Traffic Signals</div> <div>Vehicle Lighting</div> <div>Rail</div> <div>Obstruction Lighting</div> <div>Hazardous Area Lighting</div> <div>Heliport Lighting</div> </div> <div> <div>how to purchase</div> <div> <div>sales contacts</div> <div>stock check</div> </div> <div> <div>search</div> <div> <div>Product Line Search</div> <div>Please select a Product Line to search.</div> <div>Circuit Board Indicators</div> <div>find</div> </div> <div> <div>Part # / Text Search</div> <div> <div>Part No.:</div> <div>Text Search:</div> <div>search</div> </div> <div> <div>quick links</div> <div> <div>Dialight Corporate Video</div> <div> <div>Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File</div> <div>Application Notes</div> <div>FAQs</div> </div> <div> <div>Dialight Ltd (UK)</div> <div>Dialight Garufo</div> <div>Dialight BLP</div> <div>LumiDrives</div> </div> </div> </div> </div></div></div>	<div>Circuit Board Indicators - Through Hole Indicators</div> <div> <div>P/N# 5510803F</div> <div>3 mm Lens Single Color</div> </div> <div> <div>Description</div> <div>Package Options</div> <div>Product Type</div> <div>Sub Product Type</div> <div>Configuration</div> <div>Lamp Type</div> <div>Viewing</div> <div>Viewing Angle</div> <div>Test Current (mA)</div> <div>Forward Current (mA)</div> <div>LED Centerline</div> <div>Polarity</div> </div> <div> <div>3 mm CBI</div> <div>100 Pieces Per Bag</div> <div>Through Hole Indicators</div> <div>with Single Housing</div> <div>3 mm Lens</div> <div>Single Color</div> <div>Right Angle</div> <div>70</div> <div>10mA</div> <div>20mA</div> <div>2.54</div> <div>Cathode Right</div> </div>	
	<div>Absolute Maximum Ratings</div> <div>(Ta = 25 °)</div> <div> <div>Derating</div> <div>Reverse Voltage</div> <div>Solder Temp</div> <div>Operating Temp</div> <div>Storage Temp</div> </div> <div> <div>from 50Â° @ .44 mA/Â°C</div> <div>5 V</div> <div>260Â° for 5 sec</div> <div>-55 to +100° C</div> <div>-55 to +100° C</div> </div>	
	<div> <div>RoHS /pB Free</div> <div>view PDF</div> </div>	
	<div>Operating Characteristics</div> <div> <div>LED Position</div> <div>Color</div> <div>Lamp Type</div> <div>LED Type</div> <div>Intensity Min (mcd)</div> <div>Intensity Typ (mcd)</div> <div>Intensity Max (mcd)</div> <div>Fwd Voltage Min</div> <div>Fwd Voltage Typ</div> <div>Fwd Voltage Max</div> <div>Dom Wavelength Min (nm)</div> <div>Dom Wavelength Typ (nm)</div> <div>Dom Wavelength Max (nm)</div> <div>Power Dissipation Max (mW)</div> <div>Backlighting</div> <div>Pitch Between Vertical</div> <div>Pitch Between Horizontal</div> <div>Lum Intensity Min</div> <div>Lum Intensity Typ</div> <div>Lum Intensity Max</div> </div> <div> <div>Blue</div> <div>Single Color</div> <div>High Efficiency</div> <div>7.1</div> <div>12.5</div> <div>18.0</div> <div></div> <div></div> <div></div> <div>465</div> <div></div> <div></div> <div>90</div> <div>Yes</div> <div></div> <div></div> <div></div> <div></div> <div></div> </div>	

Distributor Stock Check

Check stock with our distributors now.

5510803F

check stock