



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'HSTT400-48-2C'

Your search criteria matched only one product, shown below

HSTT400-48-2C



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets Mil Spec AMSDTL-23053/5 Class 1(Colors), Class 2 (Clear)

	Part Number	HSTT40048-2C
	RoHS Compliancy Status	Compliant
	Part Description	Thin Wall Polyolefin Heat Shrink
	Material	Flame retardant polyolefin cross-linked except clear
	Color	Clear
	Military Specification	AMS-DTL-23053/5 Class 2
	Length (ft.)	4
	Length (m)	1.2
	Max. Recovered I.D. (In.)	2.00
	Max. Recovered I.D. (mm)	50.8
	Min. Expanded I.D. (In.)	4.00
	Min. Expanded I.D. (mm)	101.6
	Nominal Diameter / Size	4.00
	Nominal Recovered Wall Thickness (In.)	.055
	Nominal Recovered Wall Thickness (mm)	1.4
	Pricing Description	Heat Shrink Thin, 4"(101.6mm) Dia, Clear
	Shrink Ratio	2:1
	Temperature Range	-67°F to 275°F (-55°C to 135°C)
	Min. Order UOM	PC
	Min. Order Qty.	2
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.