

Programming adapter - MCR-PAC-T-USB - 2309000

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Software adapter cable, 2.4 m for programming MCR-...-LP-...- and MCR-...-HT-... modules



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.0 g
Custom tariff number	84718000
Country of origin	Germany

Technical data

Dimensions

Width	56 mm
Height	24.5 mm
Depth	80 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C

General

Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2
Housing material	ABS

Standards and Regulations

Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2

Programming adapter - MCR-PAC-T-USB - 2309000

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	27242208
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	19059205

ETIM

ETIM 3.0	EC000310
ETIM 4.0	EC001408
ETIM 5.0	EC001408

UNSPSC

UNSPSC 6.01	26121604
UNSPSC 7.0901	26121604
UNSPSC 11	26121604
UNSPSC 12.01	26121604
UNSPSC 13.2	26121604

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Programming adapter - MCR-PAC-T-USB - 2309000

Approvals

EAC
