



Network and Electrical Solutions
UNIFIED PHYSICAL INFRASTRUCTURESM



- Home
- Industries
- Solutions
- Products
- Partners
- Support
- About Us
- Careers

Entire Site

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips ☐ Within Results

Text Search: 'HSTT09-C2'

Your search criteria matched only one product, shown below

HSTT09-C2



- Flexible Ployolefin DRY-SHRINKTMHeat Shrink Tubing
- General Purpose heat shrink tubing for dry locations
 - Applications include insulating, protecting, harnessing and identifying wires.
 - Material Type: Crosslinked Polyolefin
 - Shrink Ratio: 2:1
 - Temperature Range: -67°F to 275°F (-55°C to 135°C)
 - Flammability Rating: Flame retardant EXCEPT clear
 - Voltage: 600 V
 - UL Recognized, CSA Certified
 - Mil Spec: AMS-DTL-23053/5 Class 1 (Colors) Class 2 (Clear)

▪ Part Number	HSTT09-C2
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Thin Wall Polyolefin Heat Shrink
▪ Material	Polyolefin cross-linked
▪ Color	Red
▪ CSA Certified	Yes
▪ Military Specification	AMS-DTL-23053/5 Class 1

▪ UL Recognized	E122770
▪ Flammability Rating	Flame Retardant
▪ Length Per Reel (ft.)	100
▪ Length Per Reel (m)	30.5
▪ Max. Recovered I.D. (In.)	.046
▪ Max. Recovered I.D. (mm)	1.2
▪ Min. Expanded I.D. (In.)	.093
▪ Min. Expanded I.D. (mm)	2.4
▪ Nominal Diameter / Size	.093
▪ Nominal Recovered Wall Thickness (In.)	.020
▪ Nominal Recovered Wall Thickness (mm)	.5
▪ Pricing Description	Heat Shrink Thin, .09"(2.4mm) Dia, Red
▪ Shrink Ratio	2:1
▪ Temperature Range	-67°F to 275°F (-55°C to 135°C)
▪ Min. Order UOM	RL
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.