

Inline function terminal - IB IL RS 232-PRO-PAC - 2878722

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline RS-232 function terminal, for serial data transmission, complete with accessories (connector and labeling field), 1 serial input and output channel in RS-232 design, dedicated process data communication

Product Description

The serial inline communication terminal IL RS-232-PRO permits simple and fast integration of scanners, scales and printers into existing production processes.

Parameter setting and data exchange is performed exclusively with process data. This means faster communication times for small data volume than with the PCP version. A wide range of applications is supported thanks to various protocols and transmission speeds up to 38400 baud.

Product Features

- One serial RS-232 input and output channel
- Various protocols supported
- Diagnostic and status indicators



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	160.0 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	24.4 mm
Height	136 mm
Depth	71.5 mm

General

Inline function terminal - IB IL RS 232-PRO-PAC - 2878722

Technical data

General

Number of plugs	2
Color	green
Weight	135 g
Mounting type	DIN rail
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	10 % ... 95 % (according to DIN EN 61131-2)
Degree of protection	IP20
Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Interfaces

Interface	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kBit/s
Interface	RS-232
Connection method	Spring-cage connection
Transmission speed	110 Bit/s ... 38400 Bit/s (configurable)
Input buffer	4 kByte
Output buffer	1 kByte
Data bits	7 or 8
Stop bits	1 or 2

Power supply

Communications power U_L	7.5 V DC (via voltage jumper)
I/O voltage	24 V DC (via voltage jumper)
I/O voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)

Serial input/output channel

Parity	Even, odd or no parity
Transmission type	Transparent mode, end-end mode, dual buffer mode, 3964R, XON/XOFF

Inline potentials

Communications power U_L	7.5 V (via voltage jumper)
Current consumption from U_L	typ. 155 mA
	max. 225 mA (all connections of the serial interface are short-circuited)

Inline function terminal - IB IL RS 232-PRO-PAC - 2878722

Classifications

eCl@ss

eCl@ss 4.0	27250304
eCl@ss 4.1	27250203
eCl@ss 5.0	27250304
eCl@ss 5.1	27242608
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27242605

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001601

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Listed / cUL Listed / LR / BV / ABS / RINA / BSH / BSH / EAC / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

Inline function terminal - IB IL RS 232-PRO-PAC - 2878722

Approvals

UL Listed 

cUL Listed 

LR

BV

ABS

RINA

BSH

BSH


EAC

cULus Listed 


Drawings

Inline function terminal - IB IL RS 232-PRO-PAC - 2878722

Connection diagram



Dimensional drawing



Block diagram

