



Home> Products > MICRO SWITCH™ Toggle Switches> NT> Product Page

32NT291 -5E



Actual product appearance may vary.

NT Series Toggle Switch, 2 pole, 3 position, Quick Connect terminal, Locking Lever

Features

Completely sealed switching chamber  
NEMA 3, 3R, 4, and 13  
UL recognized, File E12252, Vol. 1, Section 44  
CSA certified, File LR4442  
CE approved

Potential Applications

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes  
Construction equipment  
Agriculture equipment  
Material-handling equipment  
Factory-floor control units  
Machine tool equipment manufacturers

Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behind-the-panel hardware, provides uniform panel height, and provides a panel to cover seal.

Supporting Documentation

- [Accessory: Seals](#)
- [Accessory: Nuts](#)
- [Engineering Drawing](#)

Product Specifications			
Circuitry/Operating action	<div><div>Keyway</div><div>Momentary Position</div><div></div><div>123</div><div>654</div><div>ON</div></div> <div><div>Center</div><div>Position</div><div></div><div>123</div><div>654</div><div>OFF</div></div> <div><div>Opposite Keyway</div><div>Position</div><div></div><div>123</div><div>654</div><div>ON</div></div>		
Product Type	MICRO SWITCH™ Toggle Switch		
Lever Lock	<div></div> <div>Locked in center position</div>		
Ampere/Voltage Range (Resistive Load)	0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 18 A at 0.5 Vdc to 28 Vdc,0.5 A at 250 Vdc,0.75 A at 115 Vdc		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Quick Connect		
Lever Type	Locking		
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp -250, 277 Vac; 3 A - 125 Vac "L"		
Comment	Yellow coated leverlock		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	NT		

My Links

Login to iCOM  
Login as Rep/AD  
Login as Guest  
Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (\*) to expand search

Specification Search