

nanoLC module - NLC-MOD-RS232 - 2701179

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RS-232 connection for data transfer or software configuration

Product Description

Slot 1 option module. Connects the Nanoline controller to an RS-232 device. Transfers application or data or both.

Your advantages

- ✓ Watchdog timer monitors communication, providing either a warning or fault
- ✓ Password control can limit access: read-only or read/write
- ✓ Serial modules provide a PC connection for configuration purposes and downloading/uploading projects to a basic unit
- ✓ All I/O points, registers, flags, timers, counters, and system flags can be read and written remotely and independently of the program. This enables Nanoline to be used as a simple Modbus I/O block.

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 324649
GTIN	4046356324649
Weight per Piece (excluding packing)	41.400 g
Custom tariff number	85366990
Country of origin	India

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

nanoLC module - NLC-MOD-RS232 - 2701179

Technical data

Dimensions

Width	24.5 mm
Height	25.5 mm
Depth	49 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Interfaces

Interface	RS-232
Connection method	RJ11, shielded
Transmission length	4 m (bei 115 kBaud)

Supply

Supply voltage	24 V DC (Power available via logic module)
Max. current consumption	18 mA
Typical current consumption	10 mA

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	27250315
eCl@ss 4.1	27250315
eCl@ss 5.0	27242216
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242216
eCl@ss 8.0	27242216
eCl@ss 9.0	27242216

ETIM

ETIM 2.0	EC001417
ETIM 3.0	EC001417
ETIM 4.0	EC001417

nanoLC module - NLC-MOD-RS232 - 2701179

Classifications

ETIM

ETIM 5.0	EC001417
ETIM 6.0	EC001417
ETIM 7.0	EC001417

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	39122329

Approvals

Approvals

Approvals

UL Listed / EAC

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
-----------	---	---	---------------

EAC		EAC-Zulassung
-----	---	---------------

Accessories

Accessories

Cover

nanoLC module - NLC-MOD-RS232 - 2701179

Accessories

Covering hood - NLC-MOD-CAP - 2701289



Replacement cover for slot 1 in base unit.

Programming cable

Cable - NLC-PC/SERIAL-CBL 2M - 2701234



Cable, serial, 9-pos. D-SUB to RJ11/12