

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Multiple Coaxial Contacts (COAXICON)

Not EU RoHS or ELV Compliant

- Contact
- Socket
- Terminate To Coaxial Cable
- Cable Type = Belden 9221, RG 161, RG 174, RG 179, RG 179A, RG 179B, RG 188, RG 188A, RG 316
- Connector Impedance = Non-Matched ?

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [PRODUCT SPECIFICATION, CONTACT, COAXIAL, 50 OHM AND ...](#)
(PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- [Size 8 Coaxial RF 50-Ohm and Non-Impedance Mached Pi...](#) (PDF, English)
- [Extraction Tool](#) (PDF, English)

CAD Files:

- None Available

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Contact
- Pin/Socket = Socket
- Body Style = Right Angle
- Mating Contact Retention = Without
- Connector Family = AMP-HDI, Subminiature D Series 109
- Outer Shell Material = Beryllium Copper per QQ-C-530

Electrical Characteristics:

- Connector Impedance (?) = Non-Matched

Body Related Features:

- Outer Shell Plating = Bright Tin-Lead per ASTM-B-571
- Ferrule Material = Brass
- Ferrule Plating = Tin-lead

Contact Related Features:

- Contact Type = Coax
- Contact Size = 8
- Contact Mating Area Plating = Gold (30)
- Center Contact Material = Brass per QQ-B-626 and MIL-C-50

Configuration Related Features:

- Cable Type = Belden 9221, RG 161, RG 174, RG 179, RG 179A, RG 179B, RG 188, RG 188A, RG 316

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C

Conditions for Usage:

- Terminate To = Coaxial Cable

Other:

- Brand = AMP