

## Contact insert module - HC-M-DSUB 09-UT-F - 1417307


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, Number of positions: 9, Type: D-SUB-9, Socket, Screw connection, 50 V, 1 A, 0.08 mm² ... 0.5 mm², Application: Data

RoHS

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 112497
GTIN	4055626112497
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	35.7 mm
Width	34.2 mm
Length	14.6 mm

#### Electrical characteristics

Note	For HEAVYCON housing type B6 to B48, HC-M-B...MF-... module carrier frame required
Rated voltage (III/3)	50 V
Rated current	1 A
Rated surge voltage	0.8 kV
Connection profile	9

#### Ambient conditions

## Contact insert module - HC-M-DSUB 09-UT-F - 1417307

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

#### Mechanical characteristics

Conductor cross section	0.08 mm <sup>2</sup> ... 0.5 mm <sup>2</sup>
Connection cross section AWG	28 ... 20
Stripping length of the individual wire	4.2 mm
Tightening torque	0.03 Nm ... 0.05 Nm
Insertion/withdrawal cycles	≥ 500
Minimum housing height	72 mm

#### General

Type	D-SUB-9
Series	HC-M-DSUB
Color	light gray
Number of module slots	1
Connection method	Screw connection
Flammability rating according to UL 94	V0
Degree of pollution	3
Overvoltage category	III

#### Material data

Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Approvals

#### Approvals

Approvals

EAC

Ex Approvals

#### Approval details

## Contact insert module - HC-M-DSUB 09-UT-F - 1417307

### Approvals

EAC



EAC-Zulassung