

## 49153A Molded Cable Assemblies - DIN Cable Assembly

For more Information  
please call

1-800-Belden1

**General Description:**

5-position shielded DIN, used where a shielded conductor is desired and as a low cost alternative to a D-Sub, PVC insulation, foil plus braid shield, straight handle, PVC jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
5	26	19x38	TC - Tinned Copper	.020

Total Number of Conductors: 5

Number of Pins: 5

**Insulation**

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.014

**Connector Characteristics**

Connector Characteristic (not terminated) Drain Wire Solder Dip: .25 +/- .125

Connector Characteristics (not Terminated) Jacket Removal Dimension: 1 +/- .125

Connector Characteristics - First End # of Connector Contacts/positions: 5

Connector Characteristics - First End Connector Gender: Male

Connector Characteristics - First End Connector Shielding Type: Metal Backshell

Connector Characteristics - First End Connector Type: DIN

Connector Characteristics - First End Overmold Color: Black

Connector Characteristics - First End Overmold Compound Material: PVC

Connector Characteristics - First End Overmold Type: 5 Position DIN with Flex Tail

Connector Characteristics - Second End Connector Type: No Connector

**Outer Shield**

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
26	19x38	TC - Tinned Copper

**Outer Jacket**

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.037

**Overall Cable**

Overall Nominal Diameter: 0.231 in.

**Assembly Dimensional**

Assembly Dimensional Length: 10

**Wiring**

Wiring: Shield to Connector Shell

Wiring Diagram Color Code Chart:

Number	Color
--------	-------

# Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

## 49153A Molded Cable Assemblies - DIN Cable Assembly

1	Brown
2	Red
3	Orange
4	Yellow
5	Green

### Mechanical Characteristics (Overall)

UL Temperature Rating: 80°C (UL AWM Style 2464)

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC(UL) Specification:	CM (cable only)
AWM Specification:	UL Style 2464 (300 V 80°C) (cable only)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

UL Flame Test: VW-1 (Cable only)

#### Plenum/Non-Plenum

Plenum (Y/N): No

### Electrical Characteristics (Overall)

#### Max. Operating Voltage - UL:

##### Voltage

300 V RMS (UL AWM Style 2464)

### Notes (Overall)

**Notes:** Foil and braid shielded for high-noise environments. Outer jacket stripped one inch.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
49153A 010S2	1 EA	0.500 LB	BLACK		5 POS DIN STRAIGHT RI37896

Revision Number: 1 Revision Date: 09-19-2008

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.