

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Tool for processing ferrules according to DIN 46228-4, 0.5 mm² to 2.5 mm², equipped with pressure lock, magazine, cutting, stripping, twisting, and crimping unit.

Why buy this product

- ✔ Integrated pressure lock ensures consistently high-quality crimping
- ✔ Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- ✔ Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- ✔ Robust and durable due to use of resistant plastics and annealed metals
- ✔ Visualized process flows directly on the pliers simplify operation



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 042381
GTIN	4055626042381
Weight per Piece (excluding packing)	286.300 g
Custom tariff number	82032000
Country of origin	Germany

Technical data

Dimensions

Length (b)	180 mm
Width (a)	31.5 mm
Height	100 mm

General

Compression	Indent crimp
-------------	--------------

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Technical data

General

Type of contact	Ferrules
Min. AWG, flexible, multi-strand	14
AWG max., flexible, multi-strand	20
Min. cross section	0.5 mm ²
Max. cross section	2.5 mm ²
AWG min	20
AWG max	14
Maximum stripping length	11 mm
Weight	240 g

Classifications

eCl@ss

eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 8.0	21043811
eCl@ss 9.0	21043811

ETIM

ETIM 4.0	EC000168
ETIM 5.0	EC000168
ETIM 6.0	EC000168

UNSPSC

UNSPSC 13.2	27111518
-------------	----------

Accessories

Accessories

Connector

Ferrule - Al 0,5-8 WH S1 - 1200104



Taped ferrules, 0.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, white, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Accessories

Ferrule - AI 0,75- 8 GY S1 - 1200105



Taped ferrules, 0.75 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, gray, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 1,0-8 RD S1 - 1200106



Taped ferrules, 1.0 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, red, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 1,5-8 BK S1 - 1200107



Taped ferrules, 1.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, black, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - AI 2,5-8 BU S1 - 1200108



Taped ferrules, 2.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, blue, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 40 sleeves per strip.

Ferrule - AI 0,75- 8 BU S1 - 1200163



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: blue, number of strips: 10, number of sleeves per strip: 50

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Accessories

Ferrule - Al 2,5-8 GY S1 - 1200164



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: gray, number of strips: 10, number of sleeves per strip: 40

Magazine

Magazine - CRIMPFOX 4 IN 1/MAG - 1200103



Ferrule magazine for CRIMPFOX 4 IN 1, for ferrules with insulating collars from 0.5 mm² ... 2.5 mm², with a length of 8 mm