

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-BASIC

CATALOG LISTING

IXE401-6

IXE401-6

PAGE 1 OF 1

REPLACES

RELEASE NO. PR-4770

M

DRAWING
NUMBER

5

ISSUE

6

CHECK

REVISIONS

A CO-51463

KAG
23 JUL 82

B CO
57328-A

WJM
15 APR 85

C CO94274

DLM
16 MAR 99

CHECK

30 JULY 82

CHECK

02 FEB

30 JULY 82


CHECK

FORMTEK

FO-52848-A

DRAWN

ELASTOMER PLUNGER SEAL



.316 ± .010

CORROSION RESISTANT TREATED METAL ENCLOSURE

CORROSION RESISTANT STEEL PLUNGER

.050 MAX
PRETRAVEL

.060 DIA

.188 ± .020

.425 ± .020
OPERATING
POSITION

.33

.27 ELONGATED
MTG HOLE

.091 MAX DIA
MTG HOLE

COMMON

NORMALLY CLOSED

NORMALLY OPEN

.188

.214 ± .010

.616 ± .010

A ²
.070 SPHERICAL
RADIUS

72.000 +2.000
-0.000

(3) NO. 20 WIRE LEAD PER
MIL-W-22759/11 EMBEDDED
IN EPOXY CASTING RESIN

NOTES



MOUNTING HOLES WILL ACCEPT .087 MAX DIA PINS
OR SCREWS ON .188 ± .002 CENTERS




ACTUATION IN LINE WITH ARROW "A" IS RECOMMENDED



WEIGHT OF SWITCH ONLY IS .16 OZ MAX. WEIGHT OF
SWITCH WITH WIRE LEADS IS 2.23 OZ MAX

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS

OPERATING FORCE ----- 5-17 OZ

RELEASE FORCE ----- 3 OZ MIN

RELEASE TRAVEL ----- .004 MIN

DIFFERENTIAL TRAVEL ----- .005 MAX

OVERTRAVEL ----- .004 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

28 VDC

INDUCTIVE ----- SEA LEVEL ----- 0.5 AMP

RESISTIVE ----- SEA LEVEL ----- 1.0 AMP

SCALE 2:1

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X	1/.04	X	0.8/.03
ONE PLACE	X,X	0.4/.016	X,X	0.38/.015
TWO PLACES	X,X,X	0.16/.006	X,X,X	0.13/.005
THREE PLACES				
ANGLES				

DESIGN UNITS ☐ SI METRIC

US CUSTOMARY ☒

WEIGHT ³