Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF-HSTTP05-QY P
- PDF-HSTTP05-QY P
- Part Drawings
- PDF-PVC Heat Shr
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'HSTTP06-M'**

Your search criteria matched only one product, shown below

HSTTP06-MY

PVC DRY-SHRINK™ Heat Shrink Tubing in Reels
- Applications include insulating and protecting wires and cables
- Good resistance to most fuels and oils
- Voltage: 600 V
- Shrink ratio: 2:1
- Flammability: Meets UL 224 VW-1
- UL Recognized, CSA Certified
- Temperature range: -4°F to 221°F (-20°C to 105°C)
- For dry locations
- Material: Black cross-linked Polyvinyl Chloride
- Mil Spec: AMS-DTL-23053/2 Class 1
- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance

Part Number	HSTTP06-MY
RoHS Compliancy Status	Compliant
Note	HSTTP06-MY replaces HSTTP06-M
Part Description	Flexible, Flame Retardant PVC material offers good cut through and solder resistance.
Material	Polyvinyl Chloride Cross-Linked
Color	Black
CSA Certified	Yes
Military Specification	AMS-DTL-23053/2 Class 1
UL Recognized	E122770
CE Compliant	No
Flammability Rating	VW-1
Length Per Reel (ft.)	1000
Length Per Reel (m)	304.8
Max. Recovered I.D. (In.)	0.031
Max. Recovered I.D. (mm)	0.8
Min. Expanded I.D. (In.)	0.063
Min. Expanded I.D. (mm)	1.6
Nominal Diameter (In.)	0.063
Nominal Diameter (mm)	1.6
Nominal Recovered Wall Thickness (In.)	0.02
Nominal Recovered Wall Thickness (mm)	0.5
Pricing Description	Heat Shrink Thin PVC, .06"(1.6mm) Dia Black
Shrink Ratio	2:1
Temperature Range	-4°F – 221°F (-20°C – 105°C)
Type	DRY-SHRINK Thin Wall PVC Heat Shrink
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2012, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy