

1	2	3	4	5	6	7																				
A	B	C	D	E	F	G																				
<p>①</p> <p>②③</p> <p>④</p> <p>Pin 1</p> <p>Pin 4</p> <p>Conn.</p>																										
<p>③ WIRE LIST</p> <table border="1"> <thead> <tr> <th>PAIR</th> <th>COLOR</th> <th>P1</th> </tr> </thead> <tbody> <tr> <td></td> <td>RED</td> <td>1</td> </tr> <tr> <td></td> <td>WHITE</td> <td>2</td> </tr> <tr> <td>OPEN</td> <td>GREEN</td> <td>3</td> </tr> <tr> <td></td> <td>BLACK</td> <td>4</td> </tr> <tr> <td></td> <td>DRAIN</td> <td>SHELL</td> </tr> </tbody> </table>							PAIR	COLOR	P1		RED	1		WHITE	2	OPEN	GREEN	3		BLACK	4		DRAIN	SHELL		
PAIR	COLOR	P1																								
	RED	1																								
	WHITE	2																								
OPEN	GREEN	3																								
	BLACK	4																								
	DRAIN	SHELL																								
<p>④ TESTING CONDITIONS:</p> <ol style="list-style-type: none"> VOLTAGE:300V DC/0.01S. INSULATION RESISTANCE: 10 Mohms min. CONDUCTIVE RESISTANCE: 5 Ohms max. 100% OPEN AND SHORT ELECTRICAL TEST. <p>Waterproof rate:IP67</p>																										
<table border="1"> <thead> <tr> <th>ITEM</th> <th>SPECIFICATION</th> <th>Q'TY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>③</td> <td>ABS 94V-0. BLACK ,13/16"-28UN SHELLED</td> <td>12</td> <td>g</td> </tr> <tr> <td>②</td> <td>USB A/M CONNERTOR SOLDER</td> <td>1</td> <td>SET</td> </tr> <tr> <td>①</td> <td>USB 2.0 28AWG*1P+24AWG*2C+AL.MY+D+B JACKET BALCK PVC OD=5.0±0.2mm(UV RESISTANT)</td> <td>1</td> <td>PCS</td> </tr> </tbody> </table>							ITEM	SPECIFICATION	Q'TY	UNIT	③	ABS 94V-0. BLACK ,13/16"-28UN SHELLED	12	g	②	USB A/M CONNERTOR SOLDER	1	SET	①	USB 2.0 28AWG*1P+24AWG*2C+AL.MY+D+B JACKET BALCK PVC OD=5.0±0.2mm(UV RESISTANT)	1	PCS				
ITEM	SPECIFICATION	Q'TY	UNIT																							
③	ABS 94V-0. BLACK ,13/16"-28UN SHELLED	12	g																							
②	USB A/M CONNERTOR SOLDER	1	SET																							
①	USB 2.0 28AWG*1P+24AWG*2C+AL.MY+D+B JACKET BALCK PVC OD=5.0±0.2mm(UV RESISTANT)	1	PCS																							
<p>④ Customer-No.</p> <p>ASSMANN WSW-No. A-KAB-USB-A-FS-1M</p>																										
<p>③ Scale Free</p> <p>② TOLERANCE ±0.5</p>																										
<p>④ RoHS compliant</p> <p>Unit:mm</p>																										
<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>④</td> <td>Cancel "A" logo and add notes</td> <td>03.04.2018</td> <td>Tom</td> </tr> <tr> <td>③</td> <td>Update pin</td> <td>06.03.2014</td> <td>Joanna</td> </tr> <tr> <td>②</td> <td>Update</td> <td>07.07.2009</td> <td>Dean</td> </tr> <tr> <td>①</td> <td>Drawn</td> <td>19.01.2004</td> <td>Hellwig</td> </tr> </tbody> </table>							Id.	Modification	Date	Name	④	Cancel "A" logo and add notes	03.04.2018	Tom	③	Update pin	06.03.2014	Joanna	②	Update	07.07.2009	Dean	①	Drawn	19.01.2004	Hellwig
Id.	Modification	Date	Name																							
④	Cancel "A" logo and add notes	03.04.2018	Tom																							
③	Update pin	06.03.2014	Joanna																							
②	Update	07.07.2009	Dean																							
①	Drawn	19.01.2004	Hellwig																							
<p>③ ASSMANN WSW components</p> <p>② Drawing-No. ASS 1577 CA rev04</p> <p>① Replace Sheet</p>																										
H	G	F	E	D	C	B																				