



Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFFiber Optic ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips € Within Results

Text Search: 'F6PD3-3M40'

Your search criteria matched only one product, shown below

F6PD3-3M40



- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- SC Duplex Patch Cords include SC Duplex Clips to maintain polarity
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

	Part Number	F6PD33M40
	RoHS Compliancy Status	Intended for use in fixed installations which are outside the scope of RoHS
	Part Description	SC to SC multimode duplex patch cord, 3mm jacketed cable (one duplex SC connector on each end) – 62.5/125µm.
	Product Type	SC Patch Cords
	Length (m)	40
	Fiber Compatibility	62.5/125µm
	Fiber Cable Size	3mm
	Fiber Cable Type	Jacketed
	Fiber Type	Multimode
	Connector 1 Type	SC Connector
	Connector 2 Type	SC Connector
	End Configurations	SC to SC
	Fiber Count	2
	Flammability Rating	Plenum (OFNP)
	Pricing Description	SC-SC 62.5µm OFNP Dupl PC 3mm 40m
	Min. Order UOM	PC
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	€

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.