

0 601 9F6 070 – GSR 12V-15 FC

Material number	0 601 9F6 070	0 601 9F6 002	0 601 9F6 071
EAN	3165140847728		
Baretool number	3601JF6000	3601JF6000	3601JF6000
1/2 L-BOXX inlay 12 V adapters 1 600 A01 1UW	✓	✓	✓
1/2 L-BOXX inlay for tool and charger 1 600 A00 2UV	✓	✓	✓
2 x battery GBA 12 V 2.0 Ah 1 600 Z00 02X	✓		✓
Angle adapter GFA 12-W 1 600 A00 F5K	✓		
Bit holder adapter GFA 12-X 1 600 A00 F5J	✓		
Drill chuck adapter GFA 12-B 1 600 A00 F5H	✓	✓	✓
L-BOXX 102 1 600 A00 1RP	✓	✓	✓
Offset angle adapter GFA 12-E 1 600 A00 F5L	✓		
Quick charger GAL 1230 CV 1 600 A01 16B	✓		✓
Drill chuck, version	10-mm keyless chuck	10-mm keyless chuck	10-mm keyless chuck
Weight incl. battery	0,8 kg	0,8 kg	0,8 kg



Technical data

Technical data

Torque, max. (hard/soft)	30 / 15 Nm
No-load speed (1st gear / 2nd gear)	0 – 400 / 0 – 1.300 rpm
Battery type	Lithium-Ion
Chuck capacity, min./max.	1 / 10 mm
Battery voltage	12 V
Weight excl. battery	0.6 kg
Keyless chuck	10 mm
Torque settings	20+1
Length	132 mm
Height	178 mm
Cell type	Lithium-ion
Bit holder	1/4" internal hexagon

Drilling diameter

Max. drilling diameter in wood	30 mm
Max. drilling diameter in steel	10 mm

Screw diameter

Max. screw diameter	7 mm
---------------------	------

Noise/vibration information

Sound pressure level	79 dB(A)
Uncertainty K	3 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 79 dB(A); Sound power level dB (A). Uncertainty K= 3 dB.



Sales information

Positioning

- Redefine your limits – the flexibility of five solutions in one compact tool

User benefit

- Versatile: Choice of five options – drill driver with a magnetic bit holder, lockable bit holder, drill chuck, angle adapter and offset angle adapter
- Compact: Perfect for hard-to-reach places – due to extremely compact design
- Performing: Convincing power – thanks to 30 Nm of torque