

battery type: Alkaline Manganese (Mercury free)
battery size: IEC: 6LR61; JIS: 6AM6; ANSI: E; MN1604; 9V-Block
chemical system: Zn / KOH-H₂O / MnO₂

nominal voltage: 9 V
open circuit voltage: 9.2...9.8 V new battery
 9.0...9.6 V after 1 year storage at 20°C

capacity rated: 550 mAh all measurements at 20°C ambient discharge at 35mA load; 24hours/day End Voltage (EV): 5.4V

minimum: 550 mAh discharge at 10mA constant current End Voltage (EV): 5.4V

375 mAh discharge at 75mA constant current End Voltage (EV): 5.4V

typical service output, initial (new batteries)

≥ 14 h discharge at 35mA constant current; EV: 5.4V discharge 24h/d

≥ 19.5 h discharge at 270Ω resistive load; EV: 5.4V discharge 1h/d

≥ 49 h discharge at 620Ω resistive load; EV: 5.4V discharge 2h/d

≥ 18.5 d discharge at 10KΩ resistive load (continuous); additional pulse load at 620Ω for 1s/h; EV: 7.5V

internal resistance: ≤ 4 Ω at 1kHz, sine wave measurement according to IEC 896-2

shelf life: 7 years under proper storage conditions


leakage resistance over discharge: no leakage 180ohms continuous discharge for 48h; ta: 20°C; RH: 60±15%
high temperature: no leakage store 20days at ta: 60°C; RH:90±5%

ambient temperature range: - 10...50 °C


recommended storage conditions: 5...25 °C ambient temperature
 45...75 % rel. humidity


mechanical specifications

cell dimensions
 length L1: 26.5 -2 mm
 length L2: 17.5 -2 mm
 length L3: 12.7 ± 0.25 mm
 height h1: 48.5 -2 mm
 weight: 45 ± 3 g



blister card dimensions: 120 x 85 mm
weight (incl. battery): 53 ± 3 g



	ANSMANN Specifications for model:	Ansmann XPower Alkaline battery 9V E-block 1pcs blister package
	data sheet no. / part no.	5015643
	Version no.	1
	author / date	Gramlich / 24.09.2012