


SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C ~ +85°C
- 4、Contact Resistance: 10mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer PA66 UL94-V0
PIN Brass Tin-plated

| Circuit | Part NO. | Dimensions mm | | |
|---------|-----------------|---------------|-------|-------|
| | | A | B | C |
| 2 | HC-XHB-2A-X-10 | 2.50 | 7.50 | 2.50 |
| 3 | HC-XHB-3A-X-10 | 5.00 | 10.00 | 3.10 |
| 4 | HC-XHB-4A-X-10 | 7.50 | 12.50 | 3.60 |
| 5 | HC-XHB-5A-X-10 | 10.00 | 15.00 | 6.10 |
| 6 | HC-XHB-6A-X-10 | 12.50 | 17.50 | 8.60 |
| 7 | HC-XHB-7A-X-10 | 15.00 | 20.00 | 11.10 |
| 8 | HC-XHB-8A-X-10 | 17.50 | 22.50 | 13.60 |
| 9 | HC-XHB-9A-X-10 | 20.00 | 25.00 | 16.10 |
| 10 | HC-XHB-10A-X-10 | 22.50 | 27.50 | 18.60 |
| 11 | HC-XHB-11A-X-10 | 25.00 | 30.00 | 21.10 |
| 12 | HC-XHB-12A-X-10 | 27.50 | 32.50 | 23.60 |
| 13 | HC-XHB-13A-X-10 | 30.00 | 35.00 | 26.10 |
| 14 | HC-XHB-14A-X-10 | 32.50 | 37.50 | 28.60 |
| 15 | HC-XHB-15A-X-10 | 35.00 | 40.00 | 31.10 |
| 16 | HC-XHB-16A-X-10 | 37.50 | 42.50 | 33.60 |
| 17 | HC-XHB-17A-X-10 | 40.00 | 45.00 | 36.10 |
| 18 | HC-XHB-18A-X-10 | 42.50 | 47.50 | 38.60 |
| 19 | HC-XHB-19A-X-10 | 45.00 | 50.50 | 41.10 |
| 20 | HC-XHB-20A-X-10 | 47.50 | 52.50 | 43.60 |

Ordering Information

HC-XHB - N*** - * - 10



| GENERAL TOLERANCE | | | 制图 DRAWING | | 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO., LTD | | | | |
|-------------------|------|--|---------------|-------|---|------------------|--------------------|-------------|-----|
| | | | DIM | TOL | 审核 CHECK | | | | |
| | | | X.X | ±0.30 | 批准 APPROVAL | 产品名称 TITLE | XHB (2.50) 单排带扣 直针 | 版本 REV. | A |
| | | | X.XX | ±0.20 | 比例 SCALE | 产品料号 PART NO. | HC-XHB-NA-X-10 | 单位 UNITS | mm |
| | | | X.XXX | ±0.10 | | | | | |
| 1 | 初版发行 | | Angle | ±3.0° | 投影 Projection | 材料 MATERIAL | | 页次 SHEET | 1/1 |