

Ordering Information:

A2008WV-XP - ** - ***
1 2 3

1.Part No.

2.Material:

(Blank): Nylon 66,UL94V-0(White)

46: Nylon 46,UL94V-0(Beige)

GWT: Nylon 66,UL94V-0(Beige),


IEC 60335-1,5th Edition

Glow Wire Capable.

3.Finish:

(Blank): Tin over Nickel

G: Gold over Nickel



SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 30mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1000V AC/minute

Pin Material: Brass

Ordering Information & Dimensions

Part No.	Dimensions(mm)	
	A	B
A2008WV-2P	2.00	6.00
A2008WV-3P	4.00	8.00
A2008WV-4P	6.00	10.00
A2008WV-5P	8.00	12.00
A2008WV-6P	10.00	14.00
A2008WV-7P	12.00	16.00
A2008WV-8P	14.00	18.00
A2008WV-9P	16.00	20.00
A2008WV-10P	18.00	22.00
A2008WV-11P	20.00	24.00
A2008WV-12P	22.00	26.00
A2008WV-13P	24.00	28.00
A2008WV-14P	26.00	30.00
A2008WV-15P	28.00	32.00
A2008WV-16P	30.00	34.00
A2008WV-17P	32.00	36.00
A2008WV-18P	34.00	38.00
A2008WV-19P	36.00	40.00
A2008WV-20P	38.00	42.00

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

REV	DESCRIPTION	DATE
A4	CHANGE THE DRAWING	2023.06.08
A3	CHANGE THE DRAWING	2022.11.28
A2	CHANGE THE DRAWING	2020.05.07
A1	ADD THE INFORMATION	2019.05.10
A0	NEW RELEASE	2005.05.10

Unit	Scale	Sheet
mm	5:1	1 of 1

TITLE	
2.00mm PITCH VERTICAL WAFER	
DRAWING NO	REV
A2008WV-XP	A4

General Tolerance
x.x±0.25
x.xx±0.20
x.xxx±0.15
ANGLES ±1°

