

Product Search Data Sheet

Please

0.5 min

(L) 5.0±0.3

.45

: Electrode

(in mm)

(W) 3.6±0.3

(2)

(3) 1.3±0.3

7±0.3

Note: This datasheet may be out of date

Please download the latest datasheet of DLW5ATZ331MQ2#from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ331MQ2%23

DLW5ATZ331MQ2#

"#" indicates a package specification code.

In Production RoHS REACH AEC-

< List of part numbers with package codes > DLW5ATZ331MQ2K DLW5ATZ331MQ2L DLW5ATZ331MQ2B

Appearance & Shape



- 1. Low profile(h=2.35mm max.)
- 2. Small size(5.0x3.6mm)
- 3 .Large Current Available (1.5Ato 4A)
- 4 . Operating Temperature Range ÷40°C to +105°C
- 5 .Reflow and Flow soldering Available

Applications

Automotive Usage	Infotainment
---------------------	--------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
К	330mm Embossed Tape	2500
L	180mm Embossed Tape	700
В	Bulk(Bag)	100

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of DLW5ATZ331MQ2#from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ331MQ2%23

DLW5ATZ331MQ2#

"#" indicates a package specification code.

Specifications

Shape	SMD	DC Resistance	0.027Ω max.
Size Code (in mm)	5036	Insulation Resistance(min.)	10ΜΩ
Size Code (in inch)	2014	Operating Temperature Range	-40°C to 105°C
Length	5.0mm	Mass(typ.)	0.14g
Length Tolerance	±0.3mm	Number of Circuit	1
Width	3.6mm	Operating Temperature Range(Self- temperature rise is included)	No
Width Tolerance	±0.3mm		
Thickness	2.2mm		
Thickness Tolerance	±0.15mm		
Common Mode Impedance (at 100MHz)	330Ω		
Common Mode Impedance (at 100MHz) Tolerance	(Тур.)		
Common Mode Impedance (at 10MHz)	20Ω		
Common Mode Impedance (at 10MHz) Tolerance	min.		
Rated Current	2.5A		
Rated Voltage	50Vdc		
Withstanding Voltage	125Vdc		
DC Resistance(max.)	0.027Ω]	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date


Please download the latest datasheet of DLW5ATZ331MQ2#from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ331MQ2%23

DLW5ATZ331MQ2#

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

