

Printed-circuit board connector - FKCN 2,5/ 2-ST-5,08 BK - 1706034

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug component, Nominal current: 12 A, Number of positions: 2, Pitch: 5.08 mm, Connection method: Push-in spring connection, Color: black, Contact surface: Tin




The figure shows an example product from the product range

Why buy this product

- ✓ Time saving push-in connection, tools not required
- ✓ Intuitive use through colour coded actuation lever
- ✓ Extremely small design for the respective conductor cross section
- ✓ Quick and convenient testing using integrated test option
- ✓ Can be combined with the MSTB 2,5 range



Key Commercial Data

Packing unit	1
GTIN	 4 046356 864398
GTIN	4046356864398
Custom tariff number	85366990

Technical data

Dimensions

Length	27.1 mm
Height	10.9 mm
Width	10.16 mm
Pitch	5.08 mm
Dimension a	5.08 mm

Printed-circuit board connector - FKCN 2,5/ 2-ST-5,08 BK - 1706034

Technical data

General

Range of articles	FKCN 2,5/..-ST
Type of contact	Female connector
Number of positions	2
Connection method	Push-in spring connection
Rated voltage (III/3)	320 V 320 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Nominal cross section	2.5 mm ²

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	1.5 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	1.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	16

Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Printed-circuit board connector - FKCN 2,5/ 2-ST-5,08 BK - 1706034

Approvals

Approval details

EAC		B.01742
-----	---	---------