

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Product Highlights:

- [View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- ### Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- [FASTON Straight Receptacles with "F" -" Crimp Feature" \(PDF, English\)](#)

Instruction Sheets:

- ? None Available

CAD Files: ([CAD Format & Compression Information](#))

- ? 2D Drawing (DXF, Version B)
- ? 3D Model (IGES, Version B)
- ? 3D Model (STEP, Version B)

List all Documents

Additional Information:

- ## ? Product Line Information

Related Products:

- ## ? Tooling

Product Type Features:

- ? Product Type = Receptacle
 ? Tab Fit (mm [in]) = 4.75 x 0.81 [.187 x .032]
 ? Receptacle Style = Straight
 ? Insulation Support = Insulation Support
 ? Wire/Cable Type = Stranded
 ? Insulation Diameter (mm [in]) = 2.29 - 3.30
 [.090 - .130]
 ? Insertion Force = Low
 ? Material = Brass
 ? Finish = None
 ? Crimp Type = "F"
 ? CSA Certified = Yes

Mechanical Attachment:

- ? Board Mount = No

Body Related Features:

- ? Weld Tab = Without
 ? Wire Range (mm [AWG]) = 0.50 - 1.40 ² [20-16]
 ? UL Rating = Listed

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- ? Packaging Method = Strip

Other:

- ? For Hermetic Header Tab = No
- ? Line = FASTON .187
- ? Brand = AMP