

FEX FEX 5628 13 G



Sample photo

Order symbol: FEX 5628 13 G
Product nbr: 4130806
Description: Enclosure, PC
Remarks: Ex e II, EN 60079; IK 4J

EAN: 6418074008077
EI. number:
 Finland: 3424669
 Electric No. 8212026502
 Denmark:
 Electric No. Italy: 7801160
 Electric No. Sweden: 4130806

Including: Base with screws for mounting plate/DIN-rail, cover with silicone gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height | Accessories: | |
|-------------|--------|-------|--------|--------------|----------------|
| mm: | 558 | 278 | 130 | EKJVT | Mounting plate |
| inch: | 22.0 | 10.9 | 5.1 | EKMVT | Mounting plate |
| | | | | EKOVT | Mounting plate |

| Materials: | |
|-------------------------------|----------------------|
| Material: | Polycarbonate |
| Base colour: | RAL 7035 -light grey |
| Cover screws material: | Polyamide |
| Cover colour: | RAL 7035 -light grey |
| Cover screws colour: | Grey |
| Gasket material: | Silicone |

| | |
|--------|----------------------|
| EKPVT | Mounting plate |
| EKTVT | Mounting plate |
| EKUVT | Mounting plate |
| EKV 12 | DIN-35 Mounting rail |
| EKV 22 | DIN-35 Mounting rail |
| EKV 32 | DIN-35 Mounting rail |

| Temperatures: | |
|-------------------------------------|----------------|
| Temperature °C (short term): | -40 ... 120 °C |
| Temperature °C (continuous): | -10 ... 80 °C |
| Temperature °F (short term): | -40 ... 250 °F |
| Temperature °F (continuous): | 14 ... 175 °F |

| Rating: |
|--|
| Ingress Protection (EN 60529): IP54 |
| Electrical insulation: Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): 1 |
| Impact Resistance (EN 50014): 4J |

| Accessories: | |
|--------------|----------------|
| EKHVT | Mounting plate |

| Certificates: |
|---------------------------|
| ATEX |
| Attestation of Conformity |

