




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

1TL887-1L



Actual product appearance may vary.

TL Series Toggle Switch, 1 pole, 3 position, Screw terminal, Locking Lever

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Features

Environmentproof sealing
 1,2, and 4 pole circuitry
 Standard and pull-to-unlock levers
 2 and 3 position, maintained and momentary toggle action
 Temperature range: -85° F to +160° F
 Completely sealed switching chamber
 Step-design case provides added space between terminals to help prevent shorting
 UL recognized, CSA certified
 CE approved

Potential Applications

Industrial machinery and equipment
 Military and commercial aviation
 Construction equipment
 Test instruments
 Agricultural machinery
 Process control
 Medical instrumentation

Description

MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

Product Specifications													
Circuitry/Operating action	<table border="0"> <tr> <td style="text-align: center;">Keyway Position</td> <td style="text-align: center;">Center Position</td> <td style="text-align: center;">Opposite Keyway Position</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td style="text-align: center;">1 2 3</td> <td style="text-align: center;">1 2 3</td> <td style="text-align: center;">1 2 3</td> </tr> <tr> <td style="text-align: center;">ON</td> <td style="text-align: center;">OFF</td> <td style="text-align: center;">ON</td> </tr> </table>	Keyway Position	Center Position	Opposite Keyway Position				1 2 3	1 2 3	1 2 3	ON	OFF	ON
Keyway Position	Center Position	Opposite Keyway Position											
1 2 3	1 2 3	1 2 3											
ON	OFF	ON											
Product Type	MICRO SWITCH™ Toggle Switch												
Lever Lock	<p>Locked out of extreme position (Keyway side)</p>												
Ampere/Voltage Range (Resistive Load)	0.5 A to 20 A at 0.5 Vdc to 28 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.75 A at 115 Vdc, 0.5 A at 250 Vdc												
Circuitry	SPDT												
Action	3 position												
Mounting	Bushing 15/32 in												
Termination	Screw												
Lever Type	Locking												
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"												
Comment	Gold Plated Contacts												
Availability	Global												
UNSPSC Code	30211908												
UNSPSC Commodity	30211908 Toggle switches												
Series Name	TL												

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search