

**PRODUCTS**

- [Rocker switches](#)
- [Pushbutton switches](#)
- [Toggle switches](#)
- [Slide switches](#)
- [Rotary switches](#)
- [Foot switches](#)
- [Tact and key switches](#)
- [Snap-action switches](#)**
- [Micro-signal switches](#)
- [ECO switches](#)
- [Sensors](#)
- [Push'n'Drive](#)
- [Systems and modules](#)
- [Accessories](#)
- [General information](#)
- [Catalog request / download](#)

**PRODUCTS** ▶ SNAP-ACTION SWITCHES

**SERIES 1050 - SUBMINIATURE SNAP-ACTION SWITCHES - TO 10 (1.5) A 250 V AC**
[◀ Show previous product](#)
[Show next product ▶](#)

1050.2102

[Drawing](#)
[Accessories](#)


Similar to original product

→ [Print data sheet](#)

Product number	1050.2102
Switching function	Changeover switch (SPDT momentary)
Number of poles	1-pole
connections	PCB terminal, sealed
Mechanical life endurance	10E6
Rating IEC	5 A 250 V AC 5E4
Rating North America	5 A 125 - 250 V AC 1/10 HP
Design	DIN 41635 B
Contact resistance (new condition)	< 100 (1 A 12 V DC) mΩ
Insulation resistance (new condition)	> 100 (500 V DC) MΩ
Proof tracking	175 PTI
Protection type	Connection IP00
Ambient temperature	-40 °C ... +100 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	FA, standard actuator
Housing description	FBTP
Connection surface	external connection tinned
Contact material	Ag
Operating force	≤ 1.5 N
Bounce time	< 5 ms
Difference travel max.	0.2 mm
Free position (FP) max.	9.3 mm
Operating position (OP)	8.4 ±0.3 mm
Permissible total travel position	7.5 mm
Approval marks	ENEC 10 / CSA / UL
Shop / Stock version	