

Item no.: 734-124
Product description: FEMALE CONNECTOR 24 POLE PIN SPACING 3.5 MM /
0.138 IN 100% PROTECTED AGAINST MISMATING WITH
CODING FINGERS



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	18.309 g
Color	light gray
No. of connection Points	24
No. of potentials	24
pole count	24
Height	13.4 mm
Height	0.528 in
Width	86.2 mm
Width	3.394 in
Depth	18.6 mm
Depth	0.732 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A

Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.08 - 1.5 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 1.5 mm²
Cross section [mm²]	0.25 - 1.5 mm²
Cross section [mm²]	0.25 - 1.5 mm²
Cross section [AWG]	28 - 14 AWG
Strip length from	6 mm
Strip length to	7 mm
Material group	I
xxx-xxx/035-000	Strain relief plate 35 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
734-124	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-124	CCA	NL5641	250	10	0,5-1,5
734-124	CSA	154112-1465035	300	10	28-14
734-124	KEMA	2077592.02	250	10	0,5-1,5
734-124	UR	E45171	250	10	28-14
734-124	UR	E45172	300	10	28-14

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected