



Sample photo

**Order symbol:** FEX 3819 13 G  
**Product nbr:** 4130802  
**Description:** Enclosure, PC  
**Remarks:** Ex e II, EN 60079; IK 4J

**EAN:** 6418074007957  
**El. number:**  
 Finland: 3424651  
 Electric No. Denmark: 8212026421  
 Electric No. Italy: 7801130  
 Electric No. Sweden: 4130802

Including: Base with screws for mounting plate/DIN-rail, cover with silicone gasket and polyamide cover screws.

Dimensions:				Accessories:	
	Length	Width	Height		
<b>mm:</b>	378	188	130	EKJVT	Mounting plate
<b>inch:</b>	14.9	7.4	5.1	EKMVT	Mounting plate
<b>Materials:</b>				EKOVT	Mounting plate
<b>Material:</b>	Polycarbonate			EKPVT	Mounting plate
<b>Base colour:</b>	RAL 7035 -light grey			EKTVT	Mounting plate
<b>Cover screws material:</b>	Polyamide			EKUVT	Mounting plate
<b>Cover colour:</b>	RAL 7035 -light grey			EKV 12	DIN-35 Mounting rail
<b>Cover screws colour:</b>	Grey			EKV 22	DIN-35 Mounting rail
<b>Gasket material:</b>	Silicone			EKV 32	DIN-35 Mounting rail
<b>Temperatures:</b>				<b>Rating:</b>	
<b>Temperature °C (short term):</b>	-40 ... 120 °C			Ingress Protection (EN 60529): IP54	
<b>Temperature °C (continuous):</b>	-10 ... 80 °C			Electrical insulation: Totally insulated	
<b>Temperature °F (short term):</b>	-40 ... 250 °F			Halogen free (DIN/VDE 0472, Part 815): 1	
<b>Temperature °F (continuous):</b>	14 ... 175 °F			Impact Resistance (EN 50014): 4J	
<b>Accessories:</b>				<b>Certificates:</b>	
EKHVT	Mounting plate			ATEX	
				Attestation of Conformity	

