

1-1740199-2 Product Details



1-1740199-2

TE Internal Number: 1-1740199-2

Active

View 3D PDF

Standard Board Mount Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- 25 Positions
- Connector Style = Plug
- PCB Mount Angle = Right Angle
- Product Series = HD 20
- With Mating Connector Lock

View all Features

Have a Question?

Chat with a Product Information Specialist



Quick Links

- Check Pricing & Availability
- Search for Tooling
- View Mating Products (7)
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- HDP20 PIN HEADER; SMT; 25 POS. HDP20 STIFTLASTE; SM... (PDF, German)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- AMPLIMITE HDP-20 SMT - Version (PDF, German)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version C)
- 3D Model (IGES, Version C)
- 3D Model (STEP, Version C)

Additional Information:

- Product Line Information

Related Products:

- Tooling
- Mating Products (7)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- PCB Mount Angle = Right Angle
- Product Series = HD 20
- Mating Connector Lock = With
- Mating Connector Lock Type = Threaded Insert, 4-40 UNC
- PCB Mount Retention = With
- Shell Type = Front Metal Shell
- Shell Size = 1
- Footprint (mm [in]) = 4.9 [.193]
- Grounding Indents = Without
- Grounding Straps = Without
- PCB Mount Style = Surface Mount
- Color Code = None
- Mounting Hole Diameter (mm [in]) = 3.10 [.122]
- Color = Black
- Shell Material = Steel

Mechanical Attachment:

- Panel Attachment = Without

Termination Related Features:

- Grounding Clips = Without
- Solder Tail Contact Plating = Tin over Nickel

Body Related Features:

- Number of Positions = 25
- PCB Mount Retention Type = Hold Down Post(s)
- Shell Plating = Tin

Contact Related Features:

- Contact Plating, Mating Area, Material = Gold Flash
- Contact Base Material = CuMg

Housing Related Features:

- Connector Style = Plug
- Housing Material = PCT - GF

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP

BOOKMARK

Corporate Information

Who We Are
Investors
News Room
Supplier Portal
Careers

Quick Links

Check Distributor Inventory
Cross Reference
Find Documents & Drawings
Product Compliance Support Center
Site Map


Customer Support

Email or Chat with Us
Find a Phone Number
Search Knowledge Base
Manage Your Account

Sign up for our eNewsletter

Enter your email address

Follow Us On:



Visit Us On:

