Product Details for 1052874 -1

No Image Available

1052874 -1

Active

SMA/QMA RF Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Jack
- Connector Type = SMA
- Terminate To Coaxial Cable
- Coaxial Cable Termination Type = Solder

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- OSM FLANGE MOUNT JACK RECEPTACLE-SOLDER POT TERMINAL (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Gender = Jack
- Connector Type = SMA
- Body Style = Straight
- Number of Panel Mount Holes = 4
- Body Material = Stainless Steel
- Body Finish = Passivated
- Center Contact = With
- Retractable Collar = Without
- Safety Wire Holes = Without
- Dielectric Material = TFE Fluorocarbon

Mechanical Attachment:

- Panel Attachment = With
- Panel Attachment Method = Flange
- Panel Attachment Style = Front Mount
- Impedance (?) = 50

Electrical Characteristics:

- Frequency = DC to 12.4 GHz
- Insulation Resistance (M?) = 10,000

Termination Related Features:

- Coaxial Cable Termination Type = Solder

Body Related Features:

- Length (mm [in]) = 14.60 [0.575]

Contact Related Features:

- Contact Type = Solder Cup
- Center Contact Material = Beryllium Copper
- Center Contact Plating = Gold

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Coaxial Cable

Other:

- Brand = AMP

© 2006 Tyco Electronics Corporation All Rights Reserved