

- Series = 4295

Configuration Features: Sections = Sinale

| <u>Sealed</u> = Yes <u>Mount Angle</u> = Vertical <u>Termination Type</u> = PCB Terminations | Adjustment Location = Side Adjustment Style = Screwdriver Slot Operating Function = Single Turn Industry Standards: ROHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C RoHS/ELV Compliance History = Converted to comply with RoHS directive | | |
|---|---|--|--|
| Electrical Characteristics: • Resistance Selection (Ω) = K • <u>Resistance (Ω)</u> = 20K • <u>Power Rating (W)</u> = 0.50 • <u>Tolerance (%)</u> = 10 | | | |
| Termination Features: • <u>Termination Post Orientation</u> = 5.0 x 2.5 | Conditions for Usage: • <u>Temperature Coefficient (ppm/°C)</u> = 100 Other: • Brand = Citec | | |

| Corporate Information | Quick Links | Customer Support | Keep Me Informed |
|-----------------------|-----------------------------------|-----------------------|---------------------------|
| Who We Are | Check Distributor Inventory | Email or Chat With Us | Receive TE News, Events & |
| Investors | Cross Reference | Find a Phone Number | Technology Updates |
| News Room | Find Documents & Drawings | Search Knowledge Base | Enter your email address |
| Supplier Portal | Product Compliance Support Center | Manage your Account | Yan I |
| Careers | Site Map | | 🕒 🖬 🚥 🛅 |

Provide Website Feedback