

Short-circuit connector - SAC-5P-M12MS BK BR 1-2-4 - 1054366

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




M12 blind plug for sensor circuit from PSR-CT safety circuits, pin 1 bridged to pins 2 and 4

Product Description

Blind plugs for each sensor circuit from the PSR-CT safety circuits.

RoHS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	250 pc
GTIN	 4 055626 698007
GTIN	4055626698007
Weight per Piece (excluding packing)	12.300 g
Sales Key	BF1GAC

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 90 °C (Plug)
---------------------------------	-------------------------

General

Number of positions	5
Color handle area	black
Coding	A - standard
Overvoltage category	II
Degree of pollution	3
Insertion/withdrawal cycles	≥ 100

Material

Flammability rating according to UL 94	HB
--	----

Standards and Regulations

Short-circuit connector - SAC-5P-M12MS BK BR 1-2-4 - 1054366

Technical data

Standards and Regulations


Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"


Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side

Dimensional drawing



Plug, M12 x 1, straight, shielded

Classifications

eCl@ss

eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 9.0	27060311

ETIM

ETIM 5.0	EC001855
ETIM 6.0	EC001855
ETIM 7.0	EC001855