

J1MSCD - 5XMS Product Details

Share

Print

Email



J1MSCD - 5XMS
(3 - 1617565 - 7)

TE Internal Number: 3 - 1617565 - 7

Active

Military/Aerospace High Performance Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ?

1MSD TO -5 Relay Series
- ?

Input Voltage = 5 VDC
- ?

Contact Arrangement = 1 Form C, SPDT, 1 C/O
- ?

Contact - Rated Current = 1 A
- ?

Non Polarized, Monostable Coil - Magnetic System

[View all Features](#)

Quick Links

- ?

[Check Pricing & Availability](#)
- ?

[Search for Tooling](#)
- ?

[Product Feature Selector](#)
- ?

[Contact Us About This Product](#)

Documentation & Additional Information	
Product Drawings: ? None Available Catalog Pages/Data Sheets: ? RELAY (PDF, English) Product Specifications: ? None Available Application Specifications: ? None Available Instruction Sheets: ? None Available CAD Files: ? None Available	Additional Information: ? Product Line Information Related Products: ? Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: ?Series = 1MSD TO -5 Relay ? Termination Type = Long Leads Electrical Characteristics: ? Input Voltage (VDC) = 5 ? Contact - Rated Current (A) = 1 ? Coil Polarity Protection Diode = Without ? Transistor Driver = Without ? Coil Resistance (?) = 125 ? MOSFET Driver = Without ? Coil Power Measurement = Milliwatts ? Coil - Rated Power (mW) = 200 ? Actuating System = DC ? Shock = 75 G's, 6ms ? Vibration = 30G's, 10 to 3000Hz Contact Features: ? Mounting Options = PC Board ? Enclosure Type = Hermetically Sealed ? Pin Configuration = .200" x .300" Spreader Pad	Configuration Features: ?Contact Arrangement = 1 Form C, SPDT, 1 C/O ? Coil - Magnetic System = Non Polarized, Monostable ? Coil Suppression Diode = With Industry Standards: ? Government/Industry Qualification = Yes ? Government/Industry Part Number = M39016/25 -041M ?RoHS/ELV Compliance = Not ELV/RoHS compliant ?Lead Free Solder Processes = Not suitable for lead free processing ? Approved Standards = M39016 Qualified, M Level Conditions for Usage: ? Temperature Range (°C) = -65 – +125 Other: ? Brand = CII

Contact Features:

?

Mounting Options = PC Board

?

Enclosure Type = Hermetically Sealed

?

Pin Configuration = .200" x .300" Spreader Pad

Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat With Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address

