

RIGHT ANGLE PLUG CRIMP TYPE

R209.357.000

CABLE 2.6/75

Series : MMS

PACKAGING

Standard	Unit	Other
100	-	Contact us

SPECIFICATION

ELECTRICAL CHARACTERISTICS

Impedance	50 Ω
Frequency	0-2 GHz
VSWR	AD + 0.000 x F(GHz) Maxi
Insertion loss	0.2 $\sqrt{F}$ (GHz) dB Maxi
RF leakage	-(NA - F(GHz)) dB Maxi
Voltage rating	50 Veff Maxi
Dielectric withstanding voltage	250 Veff mini
Insulation resistance	500 M Ω mini

CABLE ASSEMBLY

Stripping	a	b	c	d	e	f
mm	3.00	5.00	8.00	0.00	5.00	0.00

Assembly instruction : **Crimp 06**

Recommended cable(s)
RG 179
RG 187

Characteristics indicated on this data sheet are those that can be achieved with the highest performance cable. Intrinsic limitations of the cable may diminish the performance of the assembly

Cable retention

- pull off	15 N mini
- torque	NA N.cm

MECHANICAL CHARACTERISTICS

Center contact retention	
Axial force - Mating end	8 N mini
Axial force - Opposite end	8 N mini
Torque	NA N.cm mini

Recommended torque	
Mating	NA N.cm
Panel nut	NA N.cm
Clamp nut	NA N.cm
A/F clamp nut	0.000 mm

Mating life	0 Cycles mini
Weight	0.750 g

TOOLING

Part Number	Description	Hexagon
R282.235.037	CRIMPING DIES	
R282.293.000	CRIMPING TOOL	
R282.271.000	CRIMPING TOOL	3.84

OTHERS CHARACTERISTICS

ENVIRONMENTAL

Operating temperature	-40/+90 °C
Hermetic seal	NA Atm.cm3/s
Panel leakage	NA

Issue : 0322 D

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

**RADIALL**