

 [Live Product Chat](#)



✓ Active

 Add to Part List

Not EU RoHS or ELV Compliant

- Socket
- Terminal Style = Printed Circuit
- Terminal Type = Contact
- Lead Size Accepted = .41 mm
- Lead Length Accepted = .25 - 2.92 mm

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

- [SOCKET, 3 PIN PRINTED CIRCUIT](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

List all Documents

- Product Type = Socket
- Terminal Type = Contact
- Product Series = 8059 Series
- Sleeve Material = Brass
- Color = Red
- Profile = Ultra-low

- Lead Length Accepted (mm [in]) = 0.25 – 2.92 [0.010 – 0.115]
- Pin Circle Diameter (mm [in]) = 5.08 [0.200]
- Insulator Flammability Rating = UL94V-0

- Terminal Plating = Gold

- Terminal Style = Printed Circuit
- Number of Terminals = 3
- Post Diameter (mm [in]) = 0.51 [0.020]
- Socket Type = TO-5
- Terminal Material = Beryllium Copper
- Insulator Material = Glass Filled Polyamide Nylon

- Sleeve Plating = Gold

- Lead Size Accepted (mm [in]) = 0.41 [0.016]

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

- Operating Temperature ($^{\circ}\text{C}$) = $-55 - +125$

- Brand = AMP