


Features

- 45Watts peak pulse power (tp = 8/20us)
- Tiny SOD -523 package
- Solid-state silicon-avalanche technology
- Low camping voltage
- Low leakage current
- Low capacitance (Cj=0.7pF typ.)
- Protection one data/power line



Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants(PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation

Absolute Maximum Rating

Rating	Symbol	Value	Units
Peak Pulse Power (tp=8/20μs)	P _{PP}	45	Watts
Peak Pulse Current (tp=8/20μs)(note1)	I _{pp}	3.5	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2(Contact)	V _{ESD}	15 10	kV
Lead Soldering Temperature	T _L	260(10seconds)	℃
Junction Temperature	T _J	-55 to + 125	℃
Storage Temperature	T _{stg}	-55 to + 125	℃

Electrical Characteristics

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{RWM}				5.0	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	6.0	7.5		V
Reverse Leakage Current	I_R	$V_{RWM}=5V, T=25^{\circ}C$		0.1	0.5	μA
Peak Pulse Current	I_{PP}	$t_p=8/20\mu s$			3.5	A
Clamping Voltage	V_C	$I_{PP}=3.5A, t_p=8/20\mu s$			13	V
Junction Capacitance	C_j	$V_R=0V, f=1MHz$		0.6	0.9	pF

Electrical Parameters (TA = 25°C unless otherwise noted)

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current

Note: 8/20 μs pulse waveform.




Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform






Figure 4: Clamping Voltage vs. Ipp



Package outline dimensions

SOD-523



DIMENSIONS

SYMBOL	MILLIMETER		INCHES	
	MIN	MAX	MIN	MAX
A	0.50	0.70	0.020	0.028
b	0.25	0.35	0.010	0.014
C	0.07	0.20	0.0028	0.0079
D	1.10	1.30	0.043	0.051
E	0.70	0.90	0.028	0.035
H _E	1.50	1.70	0.059	0.067
L	0.15	0.25	0.006	0.010

Marking



Ordering information

Order code	Package	Base qty	Delivery mode
UMW BSD5A051U	SOD-523	3000	Tape and reel