

Product data sheet

Characteristics

NSYPLM108TG

wall-mounting enclosure polyester monobloc
IP66 H1056xW852xD350mm glazed door



Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	41.57 in (1056 mm)
Nominal width	33.54 in (852 mm)
Nominal depth	13.78 in (350 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 lock
Body type	One piece moulded with notches in the rear Built-in canopy
Door type	Transparent
Lock type	4 points lock, handle with 5 mm double bar insert

Complementary

Number of locks	1
Mounting plate description	Without mounting plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body polyester reinforced with fibreglass Door tempered glass
Color	Grey (RAL 7035)
Standards	IEC 62208 NEMA classification 4X NEMA classification 13
Product certifications	UL

Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for operation	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	03606480776427
Nbr. of units in pkg.	1
Package weight(Lbs)	72.6 lb(US) (32.93 kg)
Returnability	No
Country of origin	ES

Packing Units

Package 1 Height	34.65 in (880.000 mm)
Package 1 width	14.96 in (380.000 mm)
Package 1 Length	42.91 in (1090.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile