

CONNECTOR HOUSINGS









✓ Active

TE CONNECTIVITY (TE)

3POS, PIN DIA 8.0, PIN HSG, ASSY, SLD

HVP 800

2141230-1

TE Internal Number: 2141230-1

EU RoHS Compliant EU ELV Compliant

Connector System Wire-to-Board, Wire-to-Device

Connector Style Housing for male terminals

Sealable Yes

Number of Positions 3

Operating Temperature Range (°C) -40 – 140



PRODUCT DRAWING

German



→ 3D PDF

DOCUMENTATION

Product Drawings

3POS, PIN DIA 8.0, PIN HSG, ASSY, SLD

PDF

German

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English	
Customer View Model	
3D_IGS.ZIP	
English	
Customer View Model	
3D_STP.ZIP	
English	
Product Specifications	
Product Specification	
Packaging Instruction	
PDF	
English Control of the Control of th	
FEATURES	+
Please review product documents or contact us for the latest agency approval information.	
Please Note: Use the Product Drawing for all design activity.	
Product Type Features	
Connector System Wire-to-Board, Wire-to-Device	
Connector Style Housing for male terminals Sealable Yes	
Terminates To Wire & Cable	
Strain Relief No	
Configuration Features	
Number of Positions 3	
Number of Rows 1	
Body Features	
Color Orange	
Mechanical Attachment	
Mounting Feature Yes	
Terminal Position Assurance Yes	
Polarized Yes	
Hanna Canalistana	
Usage Conditions On prating Tampageture Bange (%C), 40, 140	
Operating Temperature Range (°C) -40 – 140	
Industry Standards	
Degree of Protection IP6K9K	
UL Flammability Rating UL 94-HB	

Other

Connector Position Assurance Capable No

Statement of Compliance

Serviceable No

Statement of Compliance

PDF